



IT Cooling Solutions

Compact Plus DX

Close Control Air Conditioning for
High-end Applications



Compact Plus DX – Precision Air Conditioning

If you have to remove high heat loads and are looking for a high quality solution that is also kind to your budget, then you have found the right solution with Compact Plus DX. The units are easy to install and, because they are accessible from the front, can be maintained without problems. Thanks to the compact form, Compact Plus DX fits in every technology room.

And: depending on the performance you need, a STULZ air conditioning system can be flexibly expanded.

Compact Plus DX precision air conditioning units will provide an ideal and economic solution to maximize the cooling efficiency.



- 1 Heat exchanger with filter
- 2 C7000 controller
- 3 Scroll compressors
- 4 Plate-type Condenser
- 5 AC fan with direct drive
- 6 Steam humidifier (optional)
- 7 Adjustable air flow through transformer

The compact Plus DX Units are available as A and G versions.

A version: Cooling system based on the DX principle, in which the heat removed from the room is discharged via an air-cooled condenser.

G version: Cooling system based on the DX principle, in which the heat removed from the room is discharged via an air-cooled plate-type condenser in the air conditioner and released to a cooling medium.

Compact Plus DX (G version)

The advantages at a glance:

- AC fans with direct drive
- STULZ C7000 controller
- High efficiency Zig-Zag filter and low pressure drop
- Front service access only
- Filter class G4, Refrigerant R407C
- **Options:**
 - C7000 Advanced Regelsystem, Refrigerant R134a, Filter class F5
 - Suitable for connection to all common BMS systems
 - Communication via internet protocols (HTTP/SNMP) SMS or e-mail
 - Alarm notification via GSM modem

Technical Data Compact Plus DX

CPD xxx A/G single-circuit		181	211	261	291	311	361	401	411	451	531
Air flow	m³/h	6,000	6,700	7,300	7,700	8,000	8,800	9,000	12,800	13,500	15,000
DX cooling capacity (total) ¹⁾ R407C	kW	18.5	21.2	27.6	30.6	31.5	36.4	40.3	42.7	47.4	53.3
DX cooling capacity (sensible) ¹⁾ R407C	kW	18.5	21.2	24.8	26.6	28.3	31.5	33.5	42.7	44.3	49.0
Compressor power ¹⁾ R407C	kW	3.7	4.2	5.5	6.2	6.2	7.2	8.2	8.2	9.3	11.2
DX cooling capacity (total) ¹⁾ R134a	kW	17.9	19.0	23.4	28.2	28.7	31.2	36.5	38.9	-	-
DX cooling capacity (sensible) ¹⁾ R134a	kW	17.9	19.0	23.4	25.7	27.2	29.5	31.9	38.9	-	-
Compressor power ¹⁾ R134a	kW	3.3	3.8	5.0	5.7	5.8	6.3	7.6	7.7	-	-
Max. available ESP	Pa	300	290	190	120	210	60	20	300	290	160
Noise level ²⁾	dBA	50.8	53.8	56.0	57.4	56.2	58.3	58.7	55.5	57.0	59.8
Fan absorbed power ³⁾	kW	1.5	1.8	2.1	2.3	2.0	2.3	2.4	3.4	3.6	4.3
Weight (A/G)	kg	382/385	383/386	403/408	407/413	489/495	488/496	488/497	570/578	572/580	572/581
Size		1	1	1	1	2	2	2	3	3	3

CPD xxx A/G dual-circuit		402	452	512	552	612	702	802	862	1062
Air flow	m³/h	12,500	13,500	15,400	17,100	17,600	18,100	20,500	22,200	24,300
DX cooling capacity (total) ¹⁾ R407C	kW	41.3	46.3	52.2	54.2	63.0	71.7	83.7	91.9	103.6
DX cooling capacity (sensible) ¹⁾ R407C	kW	41.3	44.0	46.3	51.2	58.3	62.5	74.1	80.3	88.6
Compressor power ¹⁾ R407C	kW	8.4	9.6	11.0	11.0	12.4	14.4	16.4	18.6	22.2
DX cooling capacity (total) ¹⁾ R134a	kW	37.2	41.5	44.0	46.8	57.6	62.1	75.2	-	-
DX cooling capacity (sensible) ¹⁾ R134a	kW	37.2	41.5	44.0	46.8	57.6	58.8	70.8	-	-
Compressor power ¹⁾ R134a	kW	7.8	8.6	10.2	10.0	11.6	12.6	15.2	-	-
Max. available ESP	Pa	300	290	130	120	70	20	290	190	60
Noise level ²⁾	dBA	54.9	57.0	60.6	60.6	61.5	62.2	60.6	62.3	64.4
Fan absorbed power ³⁾	kW	3.2	3.6	4.5	4.4	4.6	4.8	5.5	6.2	7.1
Weight (A/G)	kg	596/603	596/604	629/637	717/736	725/738	727/739	850/870	852/873	853/875
Size		3	3	3	4	4	4	5	5	5

CPU xxx A/G single-circuit		181	211	261	291	311	361	401	411	451	531
Air flow	m³/h	6,000	6,700	7,300	7,600	8,000	8,500	8,500	12,800	13,500	15,000
DX cooling capacity (total) ¹⁾ R407C	kW	18.5	21.2	27.6	30.6	31.5	36.2	40.0	42.7	47.4	53.3
DX cooling capacity (sensible) ¹⁾ R407C	kW	18.5	21.2	24.8	26.5	28.3	31.0	32.5	42.7	44.3	49.0
Compressor power ¹⁾ R407C	kW	3.7	4.2	5.5	6.2	6.2	7.2	8.2	8.2	9.3	11.2
DX cooling capacity (total) ¹⁾ R134a	kW	17.9	19.0	23.4	28.3	28.7	31.2	36.4	38.9	-	-
DX cooling capacity (sensible) ¹⁾ R134a	kW	17.9	19.0	23.4	25.6	27.2	29.0	31.1	38.9	-	-
Compressor power ¹⁾ R134a	kW	3.3	3.8	5.0	5.7	5.8	6.3	7.6	7.7	-	-
Max. available ESP	Pa	250	220	110	50	140	50	50	250	250	140
Noise level ²⁾	dBA	51.8	54.4	56.5	57.5	58.6	58.7	58.7	55.9	57.4	60.2
Fan absorbed power ³⁾	kW	1.8	2.0	2.3	2.5	2.4	2.5	2.5	3.6	3.9	4.5
Weight (A/G)	kg	373/376	374/377	394/399	398/404	488/495	488/495	490/496	543/551	545/553	545/554
Size		1	1	1	1	2	2	2	3	3	3

CPU xxx A/G dual-circuit		402	452	512	552	612	702	802	862	1062
Air flow	m³/h	12,500	13,500	14,900	16,800	17,300	18,000	21,200	22,400	24,000
DX cooling capacity (total) ¹⁾ R407C	kW	41.3	46.3	52.1	54.6	62.9	71.5	84.0	92.4	103.7
DX cooling capacity (sensible) ¹⁾ R407C	kW	41.3	44.0	45.6	50.9	57.8	62.3	75.5	80.9	88.1
Compressor power ¹⁾ R407C	kW	8.4	9.6	11.0	11.0	12.4	14.4	16.4	18.6	22.2
DX cooling capacity (total) ¹⁾ R134a	kW	37.2	41.5	43.8	46.7	57.4	61.9	76.5	-	-
DX cooling capacity (sensible) ¹⁾ R134a	kW	37.2	41.5	43.8	46.7	57.4	58.6	72.5	-	-
Compressor power ¹⁾ R134a	kW	7.8	8.6	10.2	10.0	11.6	12.6	15.2	-	-
Max. available ESP	Pa	250	250	150	170	120	50	220	150	50
Noise level ²⁾	dBA	56.1	58.0	60.0	60.4	61.2	62.2	62.3	63.5	64.9
Fan absorbed power ³⁾	kW	3.5	3.9	4.3	4.3	4.5	4.8	6.2	6.7	7.2
Weight (A/G)	kg	569/576	569/577	602/610	695/714	705/716	705/717	813/836	815/838	820/840
Size		3	3	3	4	4	4	5	5	5

Remarks: All data apply at 400 V/3 ph/50 Hz with 20 Pa ESP (external static pressure) for downflow units and 50 Pa ESP for upflow units

¹⁾ Return air conditions: 24°C, 50% r. h.; condensing temperature 45°C

²⁾ Noise level at 2 m distance, free field

³⁾ The electric power input of the fans must be added to the room load

Humidifier output and heating capacity						
Size		1	2	3	4	5
Max. humidifier capacity	kg/h	8	8	15	15	15
Max. no of heating steps		2	2	2	2	3
Max. overall heating capacity	kW	12	18	18	18	27
Width	mm	1,000	1,400	1,750	2,150	2,550
Height	mm	1,980	1,980	1,980	1,980	1,980
Depth	mm	890	890	890	890	890
Number of fans		1	1	2	2	3

STULZ Company Headquarters

D **STULZ GmbH**
Holsteiner Chaussee 283 · 22457 Hamburg
Tel.: +49(40)55 85-0 · Fax: +49(40)55 85 352 · products@stulz.de

STULZ Subsidiaries

- AUS** **STULZ AUSTRALIA PTY. LTD.**
34 Bearing Road · Seven Hills NSW 21 47
Tel.: +61(2)96 74 47 00 · Fax: +61(2)96 74 67 22 · sales@stulz.com.au
- CN** **STULZ AIR TECHNOLOGY SYSTEMS (SHANGHAI) CO., LTD.**
No. 999 Shen Fu Road, Min Hang District · Shanghai 201108 · P.R. China
Tel.: +86(21)54 83 02 70 · Fax: +86(21)54 83 02 71 · info@stulz.cn
- E** **STULZ ESPAÑA S.A.**
Avenida de los Castillos 1034 · 28918 Leganés (Madrid)
Tel.: +34(91)517 83 20 · Fax: +34(91)517 83 21 · info@stulz.es
- F** **STULZ FRANCE S. A. R. L.**
107, Chemin de Ronde · 78290 Croissy-sur-Seine
Tel.: +33(1)34 80 47 70 · Fax: +33(1)34 80 47 79 · info@stulz.fr
- GB** **STULZ U. K. LTD.**
First Quarter · Blenheim Rd. · Epsom · Surrey KT 19 9 QN
Tel.: +44(1372)74 96 66 · Fax: +44(1372)73 94 44 · sales@stulz.co.uk
- I** **STULZ S.P.A.**
Via Torricelli, 3 · 37067 Valeggio sul Mincio (VR)
Tel.: +39(045)633 16 00 · Fax: +39(045)633 16 35 · info@stulz.it
- IN** **STULZ-CHSPL (INDIA) PVT. LTD.**
006, Jagruti Industrial Estate · Mogul Lane, Mahim · Mumbai · 400 016
Tel.: +91(22)56 66 94 46 · Fax: +91(22)56 66 94 48 · info@stulz.in
- NL** **STULZ GROEP B. V.**
Postbus 75 · 1180 AB Amstelveen
Tel.: +31(20)54 51 111 · Fax: +31(20)64 58 764 · stulz@stulz.nl
- NZ** **STULZ NEW ZEALAND LTD.**
Office 71, 300 Richmond Rd. · Grey Lynn · Auckland
Tel.: +64(9)360 32 32 · Fax: +64(9)360 21 80 · sales@stulz.co.nz
- PL** **STULZ POLSKA SP. Z O.O.**
Budynek Mistral · Al. Jerozolimskie 162 · 02 – 342 Warszawa
Tel.: +48(22)883 30 80 · Fax: +48(22)824 26 78 · info@stulz.pl
- USA** **STULZ AIR TECHNOLOGY SYSTEMS (SATS), INC.**
1572 Tilco Drive · Frederick, MD 21704
Tel.: +1(301)620 20 33 · Fax: +1(301)662 54 87 · info@stulz-ats.com
- ZA** **STULZ SOUTH AFRICA PTY. LTD.**
P.O.Box 15687 · Lambton 1414 · Gauteng
Tel.: +27(11)873 68 06 · Fax: +27(11)873 31 36 · aftersales@stulz.co.za

IT Cooling Solutions

Close to you all over the world.

... With specialist, competent partners in our subsidiaries and exclusive sales and service partners around the world. Our five production sites are in Europe, North America and Asia.